



Solar Compounds Corporation
1201 West Blancke Street
Linden, NJ 07036 USA
Ph: 908-862-2813 Fax: 908-862-8061
Intl: Ph: (0101) 908-862-2813 Fax: (0101) 908-862-8061
www.solarcompounds.com

TECHNICAL DATA SHEET

SOLARITE KM-2725-2

DESCRIPTION: Solarite KM-2725-2 is an asphalt-based electrical encapsulation compound to be cast into cavities containing electrical components to insulate, protect, and hold them in place.

SPECIFICATIONS:

Viscosity Thermocel @ 280°F No. 27 Spindle @ 50 RPM	180 to 300 cps
Softening Point ASTM D36-26	200°F to 220°F
Penetration @ 77°F ASTM D5-29 100 Grams 5 Seconds (0.1 mm)	0 to 6
Specific Gravity	1.02

PACKAGING: 55-gallon release lined fiber drums.

**PLEASE REFER TO MATERIAL SAFETY DATA SHEET FOR FIRST AID
INFORMATION.**

**FOR CHEMICAL EMERGENCY:
CALL CHEMTREC (DAY OR NIGHT) 800-424-9300**

9/11/02