



Solar Compounds Corporation
1201 West Blancke Street
Linden, NJ 07036 USA
Ph: 908-862-2813 Fax: 908-862-8061
Intnl: Ph: (0101) 908-862-2813 Fax: (0101) 908-862-8061
www.solarcompounds.com

TECHNICAL DATA SHEET

SOLARITE KM-2774 STRAND SEAL SEMI-CONDUCTING

USE: For the sealing of strands in high voltage power cables to prevent water penetration.

DESCRIPTION: SOLARITE KM-2774 is a non-hardening sealant, composed of a synthetic elastomer, high molecular weight polyester, conductive carbon black and inert mineral fillers and fibers. Does not contain asbestos, oil, hydrocarbons, or low molecular weight plasticizers. All ingredients are virgin materials.

PHYSICAL PROPERTIES:

Color.....Black
Solids.....100%
Specific Gravity.....1.32 +/- .05
Resistivity Ohms/Unit Sq.....1000 Ohms
Penetration (.1mm).....135 to 145
(Cone, 300 Grams Load @ 77°F ASTM-D-217-48)
Melt Index 1-3 Grams @ 121°C..... .08 to .15 Grams/Minute
(Min. 2160 Gm Load, Preheat 10 Min., Run 30 Sec.)

SPECIAL PROPERTIES:

- 1) No adverse effects on electrical or physical properties of high and low density polyethylene, synthetic elastomers, cross-linked polymers, PVC, rubbers.
- 2) Non-injurious to semi-conducting shields.
- 3) Remains stable at 300°F and higher temperatures for short periods.

- 4) Non-hydroscopic, excellent resistance to water, water vapor and salt water.
- 5) Non-drying, remains plastic with no shrinkage upon aging.
- 6) Non-corrosive to metals.
- 7) Resistant to oil.
- 8) Non-brittle @ -40°F.
- 9) Will not melt or flow at the higher temperatures.
- 10) Good adhesion to most clean, dry surfaces.
- 11) Little to no odor, non-toxic, and non-irritating to the skin.

APPLICATION: Pumped with heavy duty, double action hydraulic drum ram equipment. Cone shaped, heated follower plate and heated delivery lines recommended.

PACKAGING: 55-gallon drums, 5-gallon pails.

IMPORTANT:

The following supersedes any provision in your company's forms, letters, and papers. **SOLAR COMPOUNDS CORPORATION** makes NO WARRANTY, WHETHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES of MERCHANTABILITY OR of FITNESS FOR A PARTICULAR PURPOSE FOR THIS PRODUCT. No statements or recommendations contained in the product literature are to be construed as inducements to infringe any relevant patent, now or thereafter in existence. UNDER NO CIRCUMSTANCES SHALL **SOLAR COMPOUNDS CORPORATION** BE LIABLE FOR INCIDENTAL, CONSEQUENTIAL OR OTHER DAMAGES FROM ALLEGED NEGLIGENCE, BREACH of WARRANTY, STRICT LIABILITY OR ANY OTHER THEORY, ARISING OUT of THE USE OR HANDLING of THIS PRODUCT. The sole liability of **SOLAR COMPOUNDS CORPORATION** for any claims arising out of the manufacture, use or sale of its products shall be to refund the buyer's purchase price, provided such products have been demonstrated in **SOLAR COMPOUNDS CORPORATION'S** sole opinion, to justify such refund.

HEALTH CAUTION:

Please refer to Material Safety Data Sheet before using these products.

**PLEASE REFER TO MATERIAL SAFETY DATA SHEET FOR FURTHER FIRST
AID INFORMATION.**

FOR CHEMICAL EMERGENCY
CALL CHEMTREC (DAY OR NIGHT) 800-424-9300.

6/03