



Solar Compounds Corporation
1201 West Blancke Street
Linden, NJ 07036
Ph: 908-862-2813 Fax: 908-862-8061
www.solarcompounds.com

TECHNICAL DATA SHEET

SOLARITE KM-2745-C SILICON STRAND SEAL

USE: Recommended for the sealing of strands in water-tight and gas-block cable constructions.

DESCRIPTION: SOLARITE KM-2745-C is a silicon-base, catalyzed, heat-curable, single-component sealant.

PHYSICAL PROPERTIES:

Color.....White
Specific Gravity.....1.34 +/- .03
Pounds/Gallon.....11.2
Viscosity, Brookfield.....220,000 +/- 20,000 cps
Consistency.....Paste, Self-Leveling to Prevent Wire Channeling
Cure Temperature.....275°F Minimum
1 Minute @.....350°F
Characteristics.....Flame Retardant
Low Smoke
Catalyst.....Benzoyl Peroxide
Dielectric Constant--
ASTM-D-150.....2.95
Toxicity Index--NES713 Per
MIL-C-24643 Index/100 Gm.
5 Max.....<5
Acid Gas Generation.....None
Halogen Content.....None
Solids.....100%

APPLICATION: SOLARITE KM-2745-C may be applied in an open or closed system. Normally, the center strand is coated just prior to the closing die.

STORAGE: Six months in unopened original containers, 100°F maximum.

PACKAGING: Supplied in 1-gallon cans, 5-gallon pails, and 55-gallon drums.

IMPORTANT:

The following supersedes any provision in your company's forms, letters, and papers. **SOLAR COMPOUNDS CORPORATION** makes NO WARRANTY, WHETHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES of MERCHANTABILITY OR of FITNESS FOR A PARTICULAR PURPOSE FOR THIS PRODUCT. No statements or recommendations contained in the product literature are to be construed as inducements to infringe any relevant patent, now or thereafter in existence. UNDER NO CIRCUMSTANCES SHALL **SOLAR COMPOUNDS CORPORATION** BE LIABLE FOR INCIDENTAL, CONSEQUENTIAL OR OTHER DAMAGES FROM ALLEGED NEGLIGENCE, BREACH of WARRANTY, STRICT LIABILITY OR ANY OTHER THEORY, ARISING OUT of THE USE OR HANDLING of THIS PRODUCT. The sole liability of **SOLAR COMPOUNDS CORPORATION** for any claims arising out of the manufacture, use or sale of its products shall be to refund the buyer's purchase price, provided such products have been demonstrated in **SOLAR COMPOUNDS CORPORATION'S** sole opinion, to justify such refund.

HEALTH CAUTION:

Contact with skin and eyes should be avoided. In case of eye contact, flush with water for at least 15 minutes. Consult physician if irritation persists. For skin contact, wash in soap and water. Please refer to Material Safety Data Sheet before using these products.

PLEASE REFER TO MATERIAL SAFETY DATA SHEET FOR FURTHER FIRST AID INFORMATION.

FOR CHEMICAL EMERGENCY
CALL CHEMTREC (DAY OR NIGHT) 800-424-9300.