



Solar Compounds Corporation
1201 West Blancke Street
Linden, NJ 07036
Ph: 908-862-2813 Fax: 908-862-8061
www.solarcompounds.com

TECHNICAL DATA SHEET

SOLARITE® MW-4373
SILICON LACQUER
WATER-BASE

USE: Protective coating for braids requiring high-temperature performance, glass, fluorocarbon fibers, etc. Recommended for 600-volt appliance wires and is halogen free.

DESCRIPTION: **SOLARITE® MW-4373** rated for 200°C service. It offers excellent saturating properties, securing braids and preventing fraying or pullback, while still maintaining flexibility.

APPLICATION: A minimum of two passes suggested followed by dry/cure of 1 minute at 500°F or higher after each pass.

TYPICAL PHYSICAL CONSTANTS:

| | |
|----------------------------------|--------------|
| Solids..... | 25% +/- 1% |
| Pounds Per Gallon..... | 8.5 |
| Viscosity Brookfield @ 77°F..... | 10 +/- 5 cps |
| pH..... | 7.90 |

PACKAGING: Supplied in 1-gallon cans, 5-gallon pails, and 55-gallon drums.

SHELF LIFE: Six (6) months stored in sealed containers under frost-free conditions. Do not allow temperature to drop below 5°C.

IMPORTANT:

The following supersedes any provision in your company's forms, letters, and papers. **SOLAR COMPOUNDS CORPORATION** makes no warranty, whether expressed or implied, including warranties of merchantability or of fitness for a particular purpose for this product. No statements or recommendations contained in the product literature are to be construed as inducements to infringe any relevant patent, now or thereafter in existence. Under no circumstances shall **SOLAR COMPOUNDS CORPORATION** be liable for incidental, consequential or other damages from alleged negligence, breach of warranty, strict liability or any other theory arising out of the use of handling of this product. The sole liability of **SOLAR COMPOUNDS CORPORATION** for any claims arising out of the manufacture, use or sale of its products shall be to refund the buyer's purchase price, provided such products have been demonstrated in **SOLAR COMPOUNDS CORPORATION'S** sole opinion, to justify such refund.

HEALTH CAUTION:

Avoid breathing possible fumes, mists and vapors which can cause severe respiratory damage. Use of NIOSH approved breathing apparatus is required for more than minimal exposure. Always work in areas with adequate ventilation to allow dissipation of chemical fumes. Use of goggles, protective garments, rubber gloves, protective cream is required. Please refer to Material Safety Data Sheet before using these products.

**PLEASE REFER TO MATERIAL SAFETY DATA SHEET FOR FURTHER FIRST AID
INFORMATION.**

FOR CHEMICAL EMERGENCY
CALL CHEMTREC (DAY OR NIGHT) 800-424-9300